



Capacity	30L	50L	80L	100L
SKUS	VME-WHT-H030	VME-WHT-H050	VME-WHT-H080	VME-WHT-H100
Installation	Horizontal wall mounted	Horizontal wall mounted	Horizontal wall mounted	Horizontal wall mounted
Control type	Manual Control	Manual Control	Manual Control	Manual Control
Heating power	Single	Single	Single	Single
Material of insulation layer	PUF	PUF	PUF	PUF
Thickness of insulation layer	25mm	25mm	25mm	25mm
Protective anode	Magnesium	Magnesium	Magnesium	Magnesium
Color of finishing	White	White	White	White
Heating element	INCOLOY 840	INCOLOY 840	INCOLOY 840	INCOLOY 840
Rated power	1500W	1500W	1500W	1500W
Rated voltage	230V	230V	230V	230V
Rated frequency	50Hz	50Hz	50Hz	50Hz
Rated current	6.8A	6.8A	6.8A	6.8A
Thermostat	Capillary	Capillary	Capillary	Capillary
Temperature range	30°C to 75°C	30°C to 75°C	30°C to 75°C	30°C to 75°C
Thermal cut-off	Capillary	Capillary	Capillary	Capillary
Protection against humidity	IPX4	IPX4	IPX4	IPX4
Working Pressure	0.8MPa	0.8MPa	0.8MPa	0.8MPa
Cable length	1400mm	1400mm	1400mm	1400mm
Product size (mm)	Horizontal $\Phi$ 350×625	Horizontal $\Phi$ 390×772.5	Horizontal $\Phi$ 460×846	Horizontal $\Phi$ 460×996
Carton size (mm)	Horizontal 410*410*710	Horizontal 465*465*840	Horizontal 535*535*920	Horizontal 545*545*1065
Net weight (kg)	Horizontal 12.70	Horizontal 17.16	Horizontal 24.00	Horizontal 28.00
Gross weight (kg)	Horizontal 13.19	Horizontal 19.53	Horizontal 25.50	Horizontal 29.50
In box accessories	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1	Instruction manual*1, Safety valve*1, Hook type bolt screw*2, Dripping pipe*1